

ClubWash 500 CT™



The ClubWash 500 CT features manual zoom 7°- 28°; CMY colour mixing system; full range dimming and variable strobo effect. The ClubWash 500 CT is aimed at middle sized clubs and discotheques and various other types of installations.

● Source

- Lamp: Compact high-pressure metal halide lamp
- Base: GX9.5
- Approved models: Philips MSR 575/2, Osram HSR 575/72
- Control: Automatic and remote on/off
- Ballast: Magnetic

● Optical System

- Manual Linear zoom between 7° and 28° beam angles
- Fresnel lens of diameter 200 mm

● Electrical Specification

- Wiring options: EU model - 208/230/240V, 50/60Hz, US model - 100/120/208/230V, 50/60Hz
- Power consumption: 680VA at 230V/50Hz

● Mechanical Specification

- Height: 565 mm (22.2") - head in horizontal position
- Width: 467 mm (18.4")
- Depth: 491 mm (19.3")
- Weight: EU model - 31 kg (68.3 lbs), US model - 35 kg (77.2 lbs)

● Thermal

- Maximum ambient temperature (Ta): 40°C (104°F)
- Maximum surface temperature: 80°C (176°F)

● Control and Programming

- Protocol: USITT DMX-512
- Control channels: 11 or 13
- Built-in demo sequences
- Display: 4-digit LED display
- Pan/Tilt resolution: 8 or 16bit
- Master/Slave operation
- Stand-alone operation
- Controllable speed of fans
- Movement control: Tracking and vector
- Built-in analyzer for easy fault finding
- Data in/out: Locking 3-pin XLR

● Electromechanical Effects

- CMY colours mixing system
- Dimmer/Shutter: Full range dimming and variable strobo effect
- Manual Zoom
- Pan: 530°
- Tilt: 280°

● Rigging

- Mounting points: 4 pairs of ¼-turn locks
- Via 2 Omega holders

